

# Talrak® Tilegrout CB

## Cement based coloured tile joint filler



The Construction Alchemists

### Description

Talrak® Tilegrout CB is a ready-to-use combination of cement, filler and synthetic organic polymers. It needs just addition of prescribed amount of water at site which will result in a smooth paste.

### Features & Benefits

- Needs just addition of water at site, hence easy to apply
- Can also be used in place where there will be water stagnation like swimming pools, bathrooms etc
- Suitable vertical and horizontal application
- Economical - saves cost of multiple material storage and labour cost
- Available in standard range of colours

### Primary Application

Talrak® Tilegrout CB is used as a grout for dry tile joint in areas such as kitchen, living area, bedroom, parking area etc.

### Technical properties

Density of mixed material	1.9 - 2.0 g/cc
Pot life of mixed material	90 minutes @20°C 30 minutes @35°C
Compressive strength at 28 days	38 MPa
Tensile strength at 28 days	3 MPa

### Application Instructions

#### Surface preparation

All the tile should be tightly fixed preferably using Talrak® Tilebond FA. The surface should be free from any dust laitance and debris. The joint size between the tiles should not exceed 4mm. Talrak® Tilegrout CB should be applied only after 24hrs of fixing the tiles.

#### Mixing

Every pack of Talrak® Tilegrout CB should be mixed with 300ml of water. Add Talrak® Tilegrout CB powder to water and mix until a thick lump free paste is formed. Set aside the mixed material for 10 mins before use.

### Application

Apply Talrak® Tilegrout CB into the joints between the tiles using a putty blade. Work the mixed material into the joints and around the edges. Remove surplus material from the face of the tiles with a dry cloth and run the tip of a gloved finger or suitable rounded tool along the grout to level it off and form a profile.

When the grout is dry, clean the tiles with a damp sponge to remove any excess material. It is advisable to remove uncured grout from textured tiles prior to setting, failure to do so may result in difficulty in removal.

### Cleaning

Talrak® Tilegrout CB should be removed from tools, equipment and mixers with clean water immediately after use. Cured material can only be removed mechanically.

### Limitations

- Talrak® Tilegrout CB should be applied when the temperature is above +5°C.
- It should not be exposed to flowing water during application.

### Estimating

#### Packaging

Talrak® Tilegrout CB is supplied in 1kg pack.

### Coverage

1kg of Talrak® Tilegrout CB will cover ~25 running meter of joint size 4mm width x 5mm depth.

**Note:** The coverage figures given are theoretical. Due to wastage factors, practical coverage figures will be reduced.

### Storage

Talrak® Tilegrout CB has a shelf life of 12 months if kept in dry store in original, unopened containers. If stored at high temperature and/or high humidity conditions the shelf life may be reduced.

### Precautions

#### Health & Safety instructions

Talrak® Tilegrout CB cement based. Care should be taken to avoid inhalation of dust and contact with eyes.



**Talrak Construction Chemicals Pvt. Ltd.**

An ISO 9001:2015 Certified Company

#### Works:

Plot No. 115-A, 1st Phase. Harohalli Industrial Area,  
Kanakapura Taluka - 562 112. Ramanagar Dist.  
[www.talrak.in](http://www.talrak.in)

### Important note :

Talrak products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Talrak endeavours to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.

Ref : TCC/TDS/BP06 - R1